

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
14 April 2005 (14.04.2005)

PCT

(10) International Publication Number
WO 2005/033521 A1

(51) International Patent Classification⁷: **F04D 19/04**

West Sussex RH15 9TT (GB). **GOODWIN, David, John** [GB/GB]; BOC Edwards, Manor Royal, Crawley, West Sussex RH10 9NH (GB).

(21) International Application Number:
PCT/GB2004/004114

(74) Agent: **BOOTH, Andrew, Steven**; The Boc Group plc, Chertsey Road, Windlesham, Surrey GU20 6HJ (GB).

(22) International Filing Date:
23 September 2004 (23.09.2004)

(81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0322883.0 30 September 2003 (30.09.2003) GB

(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,


(71) Applicant (*for all designated States except US*): **THE BOC GROUP PLC** [GB/GB]; Chertsey Road, Windlesham, Surrey GU20 6HJ (GB).

(72) Inventors; and

(75) Inventors/Applicants (*for US only*): **STONES, Ian, David** [GB/GB]; BOC Edwards, York Road, Burgess Hill,

[Continued on next page]

(54) Title: VACUUM PUMP



(57) Abstract: A vacuum pump comprises a first pumping section (106), and, downstream thereof, a second pumping section (108). The pump comprises a first pump inlet (120) through which fluid can enter the pump and pass through both the first and second pumping sections towards a pump outlet, and a second pump inlet (122) through which fluid can enter the pump and pass through only the second pumping section towards the outlet. The second pumping section (108) comprises an externally threaded rotor (109).



SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*